

Truck Mounted Cranes



Model	Max lifting moment T/M	Rotating angle °	Crane weight KG
SQ2SK10/20	4.2	360° Continuous	640/818
SQ3.2SK10/20	6.72	360° Continuous	1105/1229
SQ4SK20/30	8.4/10	360° Continuous	1271/1396
SQ5SK20/30	12.5	360° Continuous	2074/2215
SQ6.3SK20/30	15.7	360° Continuous	2102/2230
SQ8SK30	20	360° Continuous	3300
SQ10SK30	25	360° Continuous	3800
SQ12SK30	30	360° Continuous	4200
SQ14SK30	35	360° Continuous	4800
SQ18SK50	45	360° Continuous	7200
SQ16SK40	43.2	360° Continuous	6020
SQ20SK50	50	360° Continuous	7200
SQ25SK20	62.5	360° Continuous	11000
SQ12K20	2	320	540
SQ22K1	3.2	370	608
SQ3.2ZK1/K2	6.72	370	1100/1150
SQ4ZK2	8.4	370	1200
SQ5ZK20/30	10.5	360° Continuous	2011/2117
SQ6.3ZK20	13.23	360° Continuous	2115/2226
SQ8ZK30	16	360° Continuous	2970
SQ10ZK30	20	360° Continuous	3477
SQ12ZK30	30	360° Continuous	4130
SQ14ZK40	35	360° Continuous	4468
SQ16ZK40	40	360° Continuous	5600
SQ25ZK60	62.5	360° Continuous	7945
SQZ800K60	70.4	360° Continuous	8560

Telescopic Forklifts



Model	Engine power kW	Max.lifting cap kg	Max.lifting height m
XT670-140/XT670-140(CE)	75	3500	13.5
XT680-170/XT680-170(CE)	82	4500	16.7

Skid Steer Loaders



Model	Engine power KW	Bucket cap. m ³	Rated load t
XT740/XT740(CE)	39.9	0.42	0.75
XT750/XT750(CE)	50.8	0.55	0.95
XT760	60	0.65	1.1

Forklifts



Model	Rated capacity kg	Lift height mm	Mast Max. extended height mm
CPCD50E	5000	3000	4419

Mini-loaders



Model	Engine power KW	Bucket cap. m ³	Rated load t
LW168G	45	0.9	1.6
LW168G(CE)	51	0.9	1.6
LW188	60	1.0	1.8

Backhoe Loaders



Model	Engine power KW	Bucket cap. m ³	Digger cap m ³
WZ30-25	65	1	0.3
XT876/XT876(CE)	82	1	0.3
XT870/XT870(CE)	82	0.8-1.2	0.25-0.35
XT860	60	0.8-1.2	0.2-0.25

Articulated Trucks



Model	Max. Engine power kW/ r/min	Max. Engine torque N.m/ r/min	Top speed(with load) Km/h
FKY30	246/2100	1674/1400	42